## **Fassmer Rescue Boats**



## **Fast all-rounders**

Fassmer fast rescue boats and rescue boats are designed to be "immediately fired up and fully available" whenever necessary.

They are the backbone of a quick, safe and successful person-over-board-manoeuver. Made for long service periods, they reduce downtimes to a minimum.

- Outboard or inboard engine
- Fixed or inflatable self-rigging devices
- Different propulsion systems available
- Fully IMO/SOLAS certified
- Top speed up to 33 knots
- Exceptional sea-keeping characteristics
- Fibreglass-reinforced polyester resin
- Soft-foam and corner fenders

| Boat Type     | LSA Code | Max. Capacity<br>(Person) | Top Speed<br>(kn) | Max. Bollard<br>pull (N) | Length (mm) | Width (mm) | Height (mm)<br>to lifting<br>connection | min.<br>Weight (kg) | Lifting Eye (LE),<br>Lifting sling (LS),<br>Release hook (RH) |
|---------------|----------|---------------------------|-------------------|--------------------------|-------------|------------|---|---------------------|---|
| RR 4.2        | 5.1      | 6                         | 6–18              | 3,600                    | 4,230       | 1,750      | 1,600                                   | 450                 | LS  |
| RR 4.5 ID     | 5.1      | 6                         | 6–10              | 3,630                    | 4,500       | 1,830      | 1,675                                   | 750                 | LE, LS, RH  |
| FRR 6.1       | 5.1      | 10                        | 20-30             | 5,000                    | 6,100       | 2,140      | 1,600                                   | 1,090               | LE, RH  |
| FRR 6.2 ID    | 5.1      | 15                        | 20-33             | 5,400                    | 6,180       | 2,260      | 1,630                                   | 1,700               | RH  |
| FRR 6.5 ID-SF | 5.1      | 15                        | 20-33             | 5,400                    | 6,460       | 2,600      | 1,630                                   | 1,800               | RH  |
| FRR 6.6 ID    | 5.1      | 17                        | 20-33             | 5,400                    | 6,680       | 2,260      | 1,630                                   | 1,900               | RH  |
| FRR 7.0 ID-SF | 5.1      | 17                        | 20-33             | 5,400                    | 6,960       | 2,600      | 1,630                                   | 1,950               | RH  |