

Clearspray Systems



The CLEARSPRAY range of oil dispersant spray systems are suitable for operation from both inshore and offshore vessels including tugs, supply vessels and workboats.

CLEARSPRAY systems are powered by an electric motor and are designed to be installed as a permanent fixture on board the spill response vessel. CLEARSPRAY systems are compatible with Spray Arms, Retractable Spray Arms for enclosed bow vessels and AFEDO™ Nozzles for the application of neat or dilute dispersant.

Product Models

The CLEARSPRAY range includes three models:

- CLEARSPRAY 50 - designed for operating from inshore vessels and produces a maximum output of 60 litres per minute.
- CLEARSPRAY 100 - designed for operating from small to medium inshore and offshore vessels and produces a maximum output of 100 litres per minute. The CLEARSPRAY 100 D2F model has ABS product design approval.
- CLEARSPRAY 150 - designed for operating from larger offshore vessels and produces a maximum

output of 150 litres per minute.

Features

Installed IP55 electric pump units

Neat and dilute dispersant application

Compatible with Spray Arms, Retractable Spray Arms and AFEDO™

Nozzles

Powder coated mild steel base plate and gunmetal and stainless steel pipework

Benefits

Reliable and robust pump units

Corrosion resistant

Neat or dilute spraying up to 30% of total outlet flow

Adjustable application rates

Precise application of dispersant with calibrated flow meters

CLEARSPRAY comes with a 1 Year Warranty