

# BETA Oil Containment Boom



Our most widely used boom for moderate to choppy waters. This versatile boom is very popular with oil containment contractors. All Beta versions are good for containing oil, flotsam, and debris.

## APPLICATIONS

- Harbors
- Rivers
- Bays
- Lagoons
- API separators
- Inland waterways
- Sheltered Water
- Canals
- Coastal areas

## BETA 1A

has no top tension cable and 1/4-inch ballast chain

### SPECIFICATIONS

Overall height, in (cm)	18 (45.7)
Float freeboard, in (cm)	6 (15.2)
Skirt draft, in (cm)	12 (30.5)
Total tensile strength, lb (kg)	5,000 (2,268)

# BETA 1B

has a 5/16-inch top tension cable and 1/4-inch ballast chain

SPECIFICATIONS	
Overall height, in (cm)	18 (45.7)
Float freeboard, in (cm)	6 (15.2)
Skirt draft, in (cm)	12 (30.5)
Total tensile strength, lb (kg)	15,000 (6,804)

# BETA 1C

has a 5/16-inch top tension cable and 5/16-inch ballast chain

SPECIFICATIONS	
Overall height, in (cm)	18 (45.7)
Float freeboard, in (cm)	6 (15.2)
Skirt draft, in (cm)	12 (30.5)
Total tensile strength, lb (kg)	17,500 (7,938)