

# EAM UXF-35



## APPROVALS

USA: FAA TSO-C13f, Type I

UK: CAA BCAR B4-8

Europe: EASA ETSO C13f, Type I

Italy: ENAC

Brazil: ANAC RBAC 21

Japan: JCAB CARJ Article 152

This single cell vest is the lightest weight aviation vest in the world, weighing only 0.9 lbs (408 grams) 5 year frequency of inspection comes standard, 10 year version available.

**Inflated Buoyancy:** 35 lbs. (156 Newtons) minimum

**Inflated Volume:** 970 cu. in. (16 liters) minimum

USA: FAA TSO-C13f, Type I

UK: CAA BCAR B4-8

Europe: EASA ETSO C13f, Type I

Italy: ENAC

Brazil: ANAC RBAC 21

Japan: JCAB CARJ Article 152

**Category of Preserver:** Adult/Child Combination

**Weight of Wearer:** 35 lbs. (15.91kg) and above

**Inflatable Buoyancy Cell:** Single Cell

**Material/Construction:** Urethane Coated Nylon fabric, RF Heat Sealed Seams

**Inflation System:** Manual CO<sub>2</sub>, Inflator and an Oral Inflation Tube

**Color:** Passenger Yellow or Crew Molten Orange

**Humidity:** Up to 95% relative humidity

**Altitude:** -2000 to 45,000 ft. above sea level

**CO<sub>2</sub> Gas Charge:** 1 x 0.073 lbs. (1 x 33 grams)

**Survivor**

**Locator** Water-activated. FAA TSO-C85 or TSO-C85a Approved.

**Light:**

**Packaging** - Flame Retardant 0.004 inch (0.1 mm) thick polyethylene bag with Tear Open Strip

**Options:** - Ten Year Extended Shelf Life Packaging

- Customized Airline Packaging

**Other** - Demonstration Vest

**Options:** - Whistle

**Service Life:** Indefinite if unit continues to pass periodic maintenance inspection

P01202-1XX Assys. - 60 months from in-service date (no later than 63 months from manufactured date) for first maintenance inspection, every 60 months for subsequent inspections

**Frequency of**

**Inspection:** P01202-2XX, P01202-3XX Assys. - 60 months from in-service date (no later than 63 months from manufactured date) for visual inspection, 10 years from date of manufacture for first maintenance inspection, every 10 years for subsequent inspections

Operational Range: -65 to 120 °F (-54 to 48.9 °C)

**Temperature:**

Storage Range: -65 to 165 °F (-54 to 73.9 °C)