

EAM UXF-35



APPROVALS

USA: FAA TSO-C13f, Type I

UK: CAA BCAR B4-8

Europe: EASA ETSO C13f, Type I

Italy: ENAC

Brazil: ANAC RBAC 21

Japan: JCAB CARJ Article 152

This single cell vest is the lightest weight aviation vest in the world, weighing only 0.9 lbs (408 grams) 5 year frequency of inspection comes standard, 10 year version available.

Inflated Buoyancy: 35 lbs. (156 Newtons) minimum

Inflated Volume: 970 cu. in. (16 liters) minimum

USA: FAA TSO-C13f, Type I

UK: CAA BCAR B4-8

Approvals: Europe: EASA ETSO C13f, Type I

Italy: ENAC

Brazil: ANAC RBAC 21

Japan: JCAB CARJ Article 152

Category of Preserver: Adult/Child Combination

Weight of Wearer: 35 lbs. (15.91kg) and above

Inflatable Buoyancy Cell: Single Cell

Material/Construction: Urethane Coated Nylon fabric, RF Heat Sealed Seams

Inflation System: Manual CO₂, Inflator and an Oral Inflation Tube
Color: Passenger Yellow or Crew Molten Orange
Humidity: Up to 95% relative humidity
Altitude: -2000 to 45,000 ft. above sea level
CO₂ Gas Charge: 1 x 0.073 lbs. (1 x 33 grams)

Survivor
Locator Water-activated. FAA TSO-C85 or TSO-C85a Approved.
Light:

Packaging Options: - Flame Retardant 0.004 inch (0.1 mm) thick polyethylene bag with Tear Open Strip
- Ten Year Extended Shelf Life Packaging
- Customized Airline Packaging

Other Options: - Demonstration Vest
- Whistle

Service Life: Indefinite if unit continues to pass periodic maintenance inspection
P01202-1XX Assys. - 60 months from in-service date (no later than 63 months from manufactured date) for first maintenance inspection, every 60 months for subsequent inspections

Frequency of Inspection: P01202-2XX, P01202-3XX Assys. - 60 months from in-service date (no later than 63 months from manufactured date) for visual inspection, 10 years from date of manufacture for first maintenance inspection, every 10 years for subsequent inspections

Temperature: Operational Range: -65 to 120 °F (-54 to 48.9 °C)
Storage Range: -65 to 165 °F (-54 to 73.9 °C)