

Switlik OPR Offshore Passage Raft

SWITLIK's OPR is designed to be a high quality, light weight, modern version of the offshore life raft, with a convertible canopy system, Toroidal Stability Device and heat sealed construction. The OPR provides 1,350 lbs. of inflated buoyancy and 24 sq. ft. of floor area and offers excellent ventilation as well as total protection from the elements.

Serious thought went into every detail and component of the OPR's design. From the soothing blue interior and ventilated canopy that help to prevent sea sickness and allow for 360° of visibility, to the reflective components and stabilizing features, the OPR was designed with your comfort and safety in mind. The OPR is vacuum sealed with an air charge inside either a soft valise or hard fiberglass container. Both options are compact enough to be carried aboard a boat of any size and handled by any passenger.

Product Features

- Four (4) wide, sturdy steps and stiffened rung ladders allow you to easily climb over the twin tubes from any side, even wearing a life jacket
- Twin independent buoyancy tubes - The high freeboard keeps the water out while the independent chambers provide redundancy in case of a tube failure
- Exterior light that is activated upon raft deployment

- SOLAS-grade reflective tape and patches located all around the raft
- Lightweight, double-coated (inside and out) urethane fabric provides superior abrasion resistance.
- Air Charge Inflation System
- Heat Sealed Technology
- Convertible Canopy System
- 5-Year Service Interval
- Stowage pocket on the valise for additional gear

Specifications:

Fiberglass Hard Case:

Weight1:	72 lb. (32.7 kg.)
Dimensions2:	31-1/2" (L) x 21-1/2" (W) x 13" (H)
Material	Hand Laid Fiberglass
Aluminum Cradle Material	AL 6463 T55

Soft Valise Case:

Weight1:	49 lb. (22.7 kg.)
Dimensions2:	24" (L) x 14" (W) x 12" (H)
Material:	Nylon Cordura

Life Raft:

Buoyancy in Fresh Water:	1324 lb. (600.6 kg.)
Buoyancy in Salt Water:	1358 lb. (616 kg.)
Inflated Raft Dimensions:	83.98" Width at flats (90.89" at corners)
Floor Area (Total):	24 sq. ft. (2.23 sq. m)
Operating Temperature Range:	-22°F to +160°F
Inflation system:	Air
Buoyancy tube fabric:	Polyurethane Coated Nylon

Standard Equipment

- Auto Deploying Sea Anchor
- Heaving Ring
- Inflatable Floor
- Knife
- Manual Inflation Pump
- Repair Clamps (2 ea.)
- Waterproof Solar Powered Flashlight

Capacity

There is no one universal method of rating raft capacities ([see here](#)). In fact, there are several different methods and governmental agencies worldwide that rate the capacity of a life raft based on the following criteria: usable floor area, inflated buoyancy, size of an average individual, and their concept of how long someone might be in the raft before rescue, not to mention how you find yourself to be there, i.e. from a sinking vessel or a ditched aircraft.

As a result, SWITLIK takes the position that a life raft's capacity is truly defined by its total size in floor area and inflated buoyancy. How many "people" that translates into depends upon your usage and interpretation of the above criteria. A raft that might safely support 6 or 8 people in an emergency for 24 hours will seem a lot smaller for a transoceanic passage where rescue might be weeks in coming.

Model Part #	Description
OPR	OPR-1330-107 OPR Life Raft, 4 Water Pockets, Soft Valise

OPR-1330-106 OPR Life Raft, TSD, Soft Valise

OPR-1330-207 OPR Life Raft, 4 Water Pockets, Hard Container

OPR-1330-206 OPR Life Raft, TSD, Hard Container

S-2260-XX OPR Cradle

S-2216 Hydrostatic Release