

# EAM-T10AS



## SPECIFICATIONS

Capacity	Rated:   Overload: 15 Persons
Approval	USA: FAA TSO-C70a, Type I Europe: EASA ETSO 2C70a, Type I Japan: JCAB CARJ Article 152
Color	Raft: Yellow Carrying case: Yellow Canopy: Fluorescent Orange R1300-2XX: Orange outside Blue inside
Diameter Raft Tube	Stabilizing Bags: Fluorescent Orange R1300-2XX: Orange outside Blue inside 11.25" (28.58 cm)
Inflated Volume: @ 1.50 psig	Tube 1: 18.01 ft³ (0.5060 m³) Tube 2: 18.01 ft³ (0.5060 m³) Canopy Arch Tube: 2.11 ft³ (0.0597 m³) Total (w/o ramp): 38.13 ft³ (1.080 m³)
Tube Volume Per Person: @ rated capacity	3.81 ft³ (0.108 m³)
Total Tube Buoyancy	1720 lbs. (780.2 kg)
Buoyancy Per Person: @ rated capacity	172 lbs. (78 kg)
Total Deck Area	36.0 ft² (3.34 m²)
Deck Area Per Person: @ rated capacity	3.60 ft² (0.334 m²)
Tube Operating Pressure	Minimum: 1.5 psig (0.10 bar) Nominal: 2.0 psig (0.14 bar) Maximum: 3.0 psig (0.21 bar)
Pressure Relief Valves	Open: 2.5 - 3.0 psig (0.17 - 0.21 bar) Close: 2.0 psig (0.14 bar)
Tube Burst Pressure	Over 6 psig (0.4 bar) Cylinder Size: 285 in³ Cylinder Type: DOT-SP11194 4500, TC-3CCM 310
Inflation System	Carbon and Glass Fiber Composite Charge Pressure: 4500 psig Charge Weights: COâ,, : 1.00 to 1.02 lbs. (0.454 to 0.463 kg) Charge Weights: Nâ,, : 2.95 to 3.10 lbs. (1.34 to 1.41 kg)
Environmental Limits	
Temperature	
Humidity	Up to 95% relative humidity
Altitude	-2000 to 45,000 ft. above sea level
Service Life	Indefinite if raft continues to pass periodic maintenance inspection
Frequency Of Inspection	36 months from the date of manufacture for first maintenance inspection, every 36 months for subsequent inspections

# APPROVALS

USA: FAA TSO-C70a, Type I

Europe: EASA ETSO 2C70a, Type I

Japan: JCAB CARJ Article 152

- For Part 91, 121, 135 Operators (GA, Corporate, Helicopter, Air Taxi)
- Twin Tube Transport Series.
- Compact, lightweight. Constructed of neoprene coated nylon.
- High tech inflation system.
- Competitively priced.