EAM-T25



SPECIFICATIONS

Rated: | Overload: 37 Persons Capacity

> USA: FAA TSO-C70a, Type I Australia: CAA CAO 103.15

Germany: LBA 40.320

Japan: JCAB CARJ Article 152

Tube: Yellow Canopy: Fluorescent Orange Carrying Case: Yellow Color

13.5" (34.3cm) **Diameter Raft Tube**

Tube 1: 38.05 ft³ (1.08 m³) Inflated Volume: @ 1.50 psig Tube 2: 38.05 ft³ (1.08 m³)

3.04 ft³ (0.0861 m³)

Total: 76.1 ft³ (2.15 m³) @ 2.0 psig

Tube Volume Per Person: @

rated capacity

Approval

Total Tube Buoyancy 4,747 lbs. (2153 kg) Buoyancy Per Person: @ rated 189.9 lbs. (86.1 kg)

capacity

Total Deck Area 90.2 ft² (8.38 m²) Deck Area Per Person: @ rated 3.61 ft² (0.335 m²)

capacity

Nominal: 2.0 psig (0.14 bar) **Tube Operating Pressure**

Open: 2.5 - 3.0 psig (0.17 - 0.21 bar) **Pressure Relief Valves**

Close: 2.0 psig (0.14 bar) Over 6 psig (0.4 bar) **Tube Burst Pressure** R0372A1XX:

Cylinder Size: 295 in³

Cylinder Type: DOT-3AA2100 & TC-3AAM161, Steel

Charge Pressure: 2100 psig

Charge Weights: COâ,,: 6.18 to 6.22 lbs. (2.80 to 2.82 kg)

Inflation System R0372A3XX:

Cylinder Size: 285 in³

Cylinder Type: DOT-SP11194 & TC-3CCM, Composite

Charge Pressure: 4500 psi

Charge Weights: COâ,, : 0.30 to 0.32 lbs (0.14 to 0.15 kg) Charge Weights: Nâ,, : 3.10 to 3.25 lbs (1.41 to 1.47 kg)

Environmental Limits

Temperature

Humidity Up to 95% relative humidity -2000 to 45,000 ft. above sea level Altitude

Indefinite if raft continues to pass periodic maintenance inspection Service Life

R0372A1XX:

12 months from in-service date or 24 months from date of manufacture for first maintenance inspection, every 12 months for subsequent inspections

Frequency Of Inspection

R0372A3XX:

36 months from last compressed gas cylinder hydro test date for first maintenance inspection, every 36 months for subsequent inspections

APPROVALS

USA: FAA TSO-C70a, Type I

Australia: CAA CAO 103.15

Germany: LBA 40.320

Japan: JCAB CARJ Article 152

- For Commercial Airlines and Air Cargo use
- Twin tube
- Compact, lightweight. Constructed of neoprene coated nylon
- High tech inflation system
- Competitively priced